

06-30-00

A



Please type a plus sign (+) inside this box [+]

PTO/SB/05 (12/97)

Approved for use through 09/30/00. OMB 0651-0032

Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No. 042390.P7017Total Pages 5First Named Inventor or Application Identifier James P. KardachExpress Mail Label No. EL627467141US

ADDRESS TO: Assistant Commissioner for Patents
 Box Patent Application
 Washington, D. C. 20231

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

1. X Fee Transmittal Form
(Submit an original, and a duplicate for fee processing)
2. X Specification (Total Pages 14)
(preferred arrangement set forth below)
 - Descriptive Title of the Invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to Microfiche Appendix
 - Background of the Invention
 - Brief Summary of the Invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claims
 - Abstract of the Disclosure
3. x Drawings(s) (35 USC 113) (Total Sheets 3)
4. Oath or Declaration (Total Pages)
 - a. Newly Executed (Original or Copy)
 - b. Copy from a Prior Application (37 CFR 1.63(d))
(for Continuation/Divisional with Box 17 completed) (**Note Box 5 below**)
 - i. DELETIONS OF INVENTOR(S) Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).
5. Incorporation By Reference (useable if Box 4b is checked)
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.
6. Microfiche Computer Program (Appendix)

The PTO did not receive the following
 listed item(s) One Copy of Transmittal Letter

06/28/00 06/28/00

a. _____ Computer Readable Copy
b. _____ Paper Copy (identical to computer copy)
c. _____ Statement verifying identity of above copies

8.	_____	Assignment Papers (cover sheet & documents(s))
9.	_____	a. 37 CFR 3.73(b) Statement (where there is an assignee)
	_____	b. Power of Attorney
10.	_____	English Translation Document (if applicable)
11.	_____	a. Information Disclosure Statement (IDS)/PTO-1449
	_____	b. Copies of IDS Citations
12.	_____	Preliminary Amendment
13.	<u> x </u>	Return Receipt Postcard (MPEP 503) (Should be specifically itemized)
14.	_____	a. Small Entity Statement(s)
	_____	b. Statement filed in prior application, Status still proper and desired
15.	_____	Certified Copy of Priority Document(s) (if foreign priority is claimed)
16.	<u> x </u>	Other: A copy of the postcard w/express mail stamp (1 pg.)

____ Continuation ____ Divisional ____ Continuation-in-part (CIP)
of prior application No: ____

_____ Customer Number or Bar Code Label
or
_____ (Insert Customer No. or Attach Bar Code Label here)

Country U.S.A. TELEPHONE (408) 720-8598 FAX (408) 720-9397

Approved for use through 09/30/00. OMB 0651-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

UNITED STATES PATENT APPLICATION

for

METHOD AND APPARATUS FOR PROVIDING REAL-TIME OPERATION IN A PERSONAL
COMPUTER SYSTEM

Inventors:

James P. Kardach

prepared by:

BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN LLP
12400 Wilshire Boulevard
Los Angeles, CA 90025-1026
(408) 720-8300

File No.: 042390.P7017

"Express Mail" mailing label number EL627467141US

Date of Deposit June 28, 2000

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Commissioner of Patents and Trademarks, Washington, D.C. 20231.

Patricia A. Balera

(Typed or printed name of person mailing paper or fee)

[Signature]

(Signature of person mailing paper or fee)

008290-5289950

METHOD AND APPARATUS FOR PROVIDING REAL-TIME OPERATION IN A PERSONAL COMPUTER SYSTEM

FIELD OF THE INVENTION

The present invention relates to computer systems; more particularly, the present invention relates to executing real-time applications at a computer system.

5 BACKGROUND

Currently, personal computers are used for various applications in order to simplify tasks to be performed by a user. Nevertheless, conventional personal computers are unable to perform real-time applications. A real-time application is one in which the correctness of computations performed by a computer not
10 only depends upon logical correctness of the computation, but also upon the time at which the result is produced. If the timing constraints are not met, the system fails. For example, in a patriot missile application, a patriot must locate an incoming missile on a radar detection system and fire a defense missile before the incoming missile can destroy its target.

15 It is difficult to execute real-time operations on conventional computer systems operating with general-purpose operating systems such as Windows 98® or Windows NT® because general-purpose operating system kernels do not have the capability to respond to events within a given time restriction. In addition, the hardware platforms of typical computer systems do not generate
20 events within the resolution of time required for execution.

In an operating system like Windows 98® there are no rules as to how application drivers are to treat events. For example, in some instances drivers

may shut off a received event for up to five seconds before the event is processed. It is apparent that such a delay would be unacceptable for a real-time operation. Therefore, it would be desirable to provide real-time function to a general purpose operating system.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will be understood more fully from the detailed description given below and from the accompanying drawings of various
5 embodiments of the invention. The drawings, however, should not be taken to limit the invention to the specific embodiments, but are for explanation and understanding only.

Figure 1 is a block diagram of one embodiment of a computer system;

Figure 2 is a block diagram of one embodiment of a processor; and

10 **Figure 3** is a flow diagram for one embodiment of the operation of an event handler.

DETAILED DESCRIPTION

A method and apparatus for providing real-time operation in a personal computer system is described. In the following detailed description of the present invention numerous specific details are set forth in order to provide a thorough understanding of the present invention. However, it will be apparent to one skilled in the art that the present invention may be practiced without these specific details. In other instances, well-known structures and devices are shown in block diagram form, rather than in detail, in order to avoid obscuring the present invention.

Figure 1 is a block diagram of one embodiment of a computer system 100. Computer system 100 includes a central processing unit (processor) 105 coupled to processor bus 110. In one embodiment, processor 105 is an Intel architecture processor in the Pentium® family of processors including the Pentium® II family and mobile Pentium® and Pentium® II processors available from Intel Corporation of Santa Clara, California. Alternatively, other processors may be used. Processor 105 may include a first level (L1) cache memory (not shown in Figure 1).

In one embodiment, processor 105 is also coupled to cache memory 107, which is a second level (L2) cache memory, via dedicated cache bus 102. The L1 and L2 cache memories can also be integrated into a single device. Alternatively, cache memory 107 may be coupled to processor 105 by a shared bus. Cache memory 107 is optional and is not required for computer system 100.

Chip set 120 is also coupled to processor bus 110. In one embodiment, chip set 120 is the 440BX chip set available from Intel Corporation; however, other chip sets can also be used. Chip set 120 may include a memory controller for controlling a main memory 113. Further, chipset 220 may also include an Accelerated Graphics Port (AGP) Specification Revision 2.0 interface 320 developed by Intel Corporation of Santa Clara, California. AGP interface 320 is coupled to a video device 125 and handles video data requests to access main memory 113.

Main memory 113 is coupled to processor bus 110 through chip set 120.

Main memory 113 and cache memory 107 store sequences of instructions that are executed by processor 105. The sequences of instructions executed by processor 105 may be retrieved from main memory 113, cache memory 107, or any other storage device. Additional devices may also be coupled to processor bus 110, such as multiple processors and/or multiple main memory devices. Computer system 100 is described in terms of a single processor; however, multiple processors can be coupled to processor bus 110. Video device 125 is also coupled to chip set 120. In one embodiment, video device includes a video monitor such as a cathode ray tube (CRT) or liquid crystal display (LCD) and necessary support circuitry.

Processor bus 110 is coupled to system bus 130 by chip set 120. In one embodiment, system bus 130 is a Peripheral Component Interconnect (PCI) bus adhering to a Specification Revision 2.1 bus developed by the PCI Special Interest

Group of Portland, Oregon; however, other bus standards may also be used.

Multiple devices, such as audio device 127, may be coupled to system bus 130.

According to one embodiment, a radio transceiver 129 is coupled to system bus 130. Radio transceiver 129 may be used to implement a communication interface
5 between computer system 100 and a remote device (not shown).

Bus bridge 140 couples system bus 130 to secondary bus 150. In one embodiment, secondary bus 150 is an Industry Standard Architecture (ISA) Specification Revision 1.0a bus developed by International Business Machines of Armonk, New York. However, other bus standards may also be used, for
10 example Extended Industry Standard Architecture (EISA) Specification Revision 3.12 developed by Compaq Computer, et al. Multiple devices, such as hard disk 153 and disk drive 154 may be coupled to secondary bus 150. Other devices, such as cursor control devices (not shown in **Figure 1**), may be coupled to secondary bus 150.

15 According to one embodiment, computer system 100 includes as a real-time operating system integrated with a general-purpose operating system. For example, computer system 100 enables processor 105 to execute real-time applications (e.g., radio communication systems) using the Windows 98® operating system developed by Microsoft Corporation of Redmond, Washington.
20 However, one of ordinary skill in the art will appreciate that computer system 100 may be implemented using other general-purpose operating systems. Real-time applications are applications that have time constraints on aspects of their

behavior. If the constraints are not met, the application either fails or needs to adapt gracefully to the operating conditions.

Figure 2 is a block diagram of one embodiment of processor 105.

Processor 105 includes an analog to digital converter (ADC) 210, a timer 220,
5 register 230, event mechanism 240 and event handler 250. ADC 210 samples real time analog data received at computer system 100 and converts the data into a digital format. According to one embodiment, ADC 210 is coupled to and receives the analog data from transceiver 129 (**Figure 1**).

10 Timer 220 is used as a mechanism to generate timer interrupts at event mechanism 240. According to one embodiment, timer 220 transmits a signal to event mechanism 240 at predetermined intervals. The signal indicates that mechanism 240 is to generate a timer interrupt. According to one embodiment, timer interrupts are generated every 5 milliseconds. However, one of ordinary skill in the art will appreciate that other time intervals may be used to generate
15 timer interrupts.

Register 230 is coupled to ADC 210. Register 230 stores data received from ADC 210 that is to later be processed at CPU 105. Event mechanism 240 is coupled to timer 220 and register 230. As described above, event mechanism 240 generates real-time timer interrupts. The timer interrupts are examined by event
20 handler 250. The timer interrupts indicate to event handler 250 when there is likely a need for real-time data too be serviced.

Event handler 250 processes real-time interrupts received from event

mechanism 240. Upon detecting a timer interrupt, event handler 250 verifies whether there is data stored in register 230 that needs to be serviced. However, prior to the service of data within register 230, event handler 250 must determine the priority of the timer interrupt relative to other interrupts received at processor 105.

Typically, interrupts are called in response to a hardware interrupt or software event. An application or device requesting service, or actually being serviced, is serviced in entirety, provided another interrupt with a higher priority requests service. According to one embodiment, if an interrupt with a higher priority requests service, the higher priority request will preempt the lower priority interrupt. The lower priority interrupt will continue upon completion of the higher priority interrupt. A timer interrupt functions in the same manner as ordinary interrupts, except that they are called in response to timer 220.

According to one embodiment, timer interrupts (e.g., real-time events) are given a high priority with respect to other events that request service at processor 105. For example, timer interrupts have a higher priority than non-critical interrupts (e.g., system management interrupts), and a lower priority than critical interrupts (e.g., non-maskable interrupts).

Figure 3 is a flow diagram of one embodiment of the operation of event handler 250 upon receiving a real-time event. At process block 310, event handler 250 receives a timer interrupt from event mechanism 240. At process block 320, event handler 250 determines whether the real-time event performed

by processor 105 has a higher priority than the current operation. If the current operation performed by processor 105 does not have a higher priority than the real-time event, the current state of processor 105 is saved, process block 330.

Therefore, the current operations being executed by processor 105 is set-aside for
5 later execution.

At process block 340, processor 105 services the real-time event. At process block 350, service of the real-time event by processor 105 is completed. At process block 360, processor 105 is returned to its state prior to receiving the timer interrupt. If the current operation performed by processor 105 does have a
10 higher priority than the real-time event, processor 105 continues servicing the current operation, process block 370.

The present invention enables processor 105 to process real-time events within an acceptable latency period. As a result, processor 105 is capable of emulating application protocols that are typically carried out by digital signal
15 processors.

Whereas many alterations and modifications of the present invention will no doubt become apparent to a person of ordinary skill in the art after having read the foregoing description, it is to be understood that any particular embodiment shown and described by way of illustration is in no way intended
20 to be considered limiting. Therefore, references to details of various embodiments are not intended to limit the scope of the claims which in themselves recite only those features regarded as the invention.

CLAIMS

What is claimed is:

- 1 1. A method comprising:
2 receiving real-time data at a personal computer implementing a general
3 purpose operating system;
4 generating a real-time event at the personal computer;
5 determining whether the real-time event has a higher priority than a first
6 event being processed at the personal computer; and
7 if so, processing the real-time event.
- 1 2. The method of claim 1 further comprising continuing to process the first
2 event if the real-time event does not have a higher priority than the first event.
- 1 3. The method of claim 1 further comprising:
2 saving the state of the first event at the personal computer prior to
3 processing the real-time event; and
4 processing the prior event after processing of the real-time event has been
5 completed.
- 1 4. The method of claim 1 further comprising:
2 receiving a second event while processing the real-time event; and
3 determining whether the second event has a higher priority than the real-

the relative priority between real-time events and non-real-time events.

12. The computer system of claim 11 wherein the CPU further comprises an analog to digital converter coupled to the register.

13. A central processing unit (CPU) comprising:

5 a timer to generate timing signals at predetermined time intervals; and
an event mechanism coupled to the timer to generate real time events,
wherein the CPU operates according to a general purpose operating system
adaptable to execute real-time instructions.

14. The computer system of claim 13 wherein the CPU further comprises an
10 event handler coupled to the event mechanism to process real-time events.

15. The computer system of claim 14 wherein the CPU further comprises a
register coupled to the event mechanism to store real-time data.

1 16. The computer system of claim 15 wherein the CPU further comprises an
2 analog to digital converter coupled to the register.

ABSTRACT

A method is disclosed. The method includes receiving real-time data at a personal computer implementing a general purpose operating system, generating a real-time event at the personal computer and determining whether
5 the real-time event has a higher priority than a first event being processed at the personal computer. If the real-time event has a higher priority than the first event being processed, the real-time event is processed.




FIGURE 2

